



FOR THE RIGHT CHEMISTRY

DINOX Handels-GmbH, Brüdertor 3, 59494 Soest/Germany

Tel: +49 (0) 2921 36 86 0
Fax: +49 (0) 2921 36 86 36
Email: info@dinox.com
Web: www.dinox.com
Datum: 17.06.2016

PRODUCT SPECIFICATION



APROVADO
DEP. DE QUALIDADE

No. 202

SODIUM PERCARBONATE, COATED

Parameter	Typical Values	Method of analysis
Appearance	white, free flowing granules	Visual
Active oxygen	min. 13,1 % (w/w)	Titration
Moisture	max. 0,5 %	Karl-Fischer
Bulk density	1 – 1,2 g/ ml	Gravimetric
Solubility (20 °C)	140 g/ l	Titration
Rate of Dissolution (60 sec, 20°C, 300 rpm)	min. 90 %	Titration
Iron (Fe)	< 10 ppm	Colorimetric
Stability (48h, 32°C, 80RH)	min. 90 %	Wet Stability
Stability (16h, 40°C)	< 10 µW/g	TAM
pH (1% solution)	10 - 10,8	pH-Meter


Grain Size distribution:

400 – 1400 µ	min. 90 %
< 400 µ	max. 10 %
> 1400 µ	max. 10 %
< 150 µ	max. 1 %
> 1600 µ	max. 1 %

Issued by:

Ute Zimmermann

Checked by:


Christina Weckerle